



Seldenrod

HEAD OFFICE: Cnr of Riley Street & Jan van Riebeeck Drive, Beaconvale 7500, Parow, South Africa
 PO BOX 6307, WELGEMOED 7538 • TEL: +27 21 932-3602 • FAX: +27 21 932-3623
 CELL: FRANK 082 573-1491 • RODGER 083 302-5530 • SELWYN 082 374-1611
 E-mail: seldenrod@seldenrod.co.za

REFLECTIVE SHEETING – ADVERTISEMENT GRADE PVC TYPE

QTM3400-135

Feature: untearable, easy operation, can be digital printed.

Application: advertisement signs, temporary work zone signs.

Service life: 3 years

Specification: 1.35m x 50m

Available color: white, yellow, red, green, blue, orange, lemon yellow, fl.yellow

Other technical datas:

1. Surface Film: PVC Type
2. Thickness of film: 0.24mm, Thickness of Glue:0.03mm
Thickness of Release Paper: 0.27mm, total thickness of products: 0.36mm
3. Weight of Release Paper: 114g/sqm
4. Type of Adhesive: Pressure-Sensitive Type
5. Strength of Adhesive: at the condition of 0.8kg, 5min, total length: 10cm, the falling Length≤ 2cm
6. Operation temperature: 10°C---30 °C
7. Working temperature: 0°C--- 50°C
8. weight per sqm: 400g
9. Color chromaticity:
Standard light source: D65 Observation condition: 45/0 Observation angle: 2 degree°

color	Color Chromaticity								Luminescence Factor
	X	Y	X	Y	X	Y	X	Y	
White	0.350	0.360	0.300	0.310	0.285	0.325	0.355	0.375	≥0.27
Yellow	0.545	0.454	0.464	0.534	0.427	0.483	0.487	0.423	0.16---0.40
Red	0.690	0.310	0.658	0.342	0.569	0.341	0.595	0.315	0.03---0.10
Green	0.007	0.703	0.026	0.399	0.177	0.362	0.248	0.409	0.03---0.10
Blue	0.078	0.170	0.137	0.038	0.210	0.160	0.150	0.220	0.01---0.10

10. Coefficient of retroreflection

Observation Angle	Entrance Angle	White	Yellow	Red	Green	Blue
0.2	-4	160	110	30	20	10

DURBAN

Unit 9,
 3 Hillhead Road,
 Mount Edgecombe
 Tel: (031) 539-7663 • Fax: (031) 539-5483

JOHANNESBURG

29 Brunton Circle
 New Founders View South
 Modderfontein
 Tel: (011) 524-0927 • Fax: (011) 609-2094