

GLITTERPRINT

Description PVC glitter heat seal material with polyester backing, created for inkjet digital printing & cutting systems with solvent, eco solvent or thermoresin based inks. The material grants a high covering power on dark fabrics as well.
Average thickness: **300 micron**

Basic information Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:
Plotter settings (eg. with ROLAND VP-300 plotter)
Blade: **new at 50°**
Minimum required pressure: **140 gf**
Transfer setup
Temperature: **165°C**
Time: **15"**
Pressure: **medium (3÷4 bar)**

Application instructions Print and cut the material
Let the print dry at least 12 hours before rolling up, overlaying or heat transferring the material
Weed the exceeding material
Remove the print from the polyester backing using Siser's T.T.D. (adhesive, transparent and resistant to high temperatures)
Heat apply
Remove the application tape warm (should you use other application tapes, follow the manufacturer's instructions)

Suitable textiles Cotton, polyester and blends of these materials
(not suited for treated and dye sublimation fabrics)

Washing instructions Wait **24h** after the heat transfer
50°C Max – inside out
Do not use bleach or other aggressive chemical agents
Dry clean: **no**
Tumble dry: **not recommended**



Siser s.r.l.

Viale della Tecnica n° 18
36100 Vicenza - Italy
Tel. +39 0444.287960
Fax +39 0444.287959
info@siser.it - www.siser.it

N.B.

All information given in this sheet are based on our experience.
We always recommend performing a test before starting standard production.
For best results we recommend to store the product away from direct sunlight.