

STRIPFLOCK®

Description Plotter cut flock heat seal material with polyester backing.
Average thickness: **500 micron**

Basic information Due to the many different base materials available on the market, the following heat transfer instructions are given as a guideline only:
Plotter settings (eg. with ROLAND GX-24 plotter)
Blade: **high thickness blade**
Minimum required pressure: **100 gf**
Transfer setup
Temperature: **160°C**
Time: **15"**
Pressure: **medium (3÷4 bar)**

Application instructions **N.B.: with special colors Cinnamon, Denim, Orchid and Emerald, we highly recommend cutting details not smaller than 1 cm**

Mirror cut the material. We recommend using high thickness blades.
Weed the exceeding material
Place the material on the garment with its polyester backing
Heat apply
Remove the support cold

Suitable textiles Cotton, polyester and blends of these materials
(not suited for treated and dye sublimation fabrics)

Washing instructions Wait **24h** after the heat transfer
60°C Max
Do not use bleach or other aggressive chemical agents
Dry clean: **no**
Tumble dry: **yes**



Siser s.r.l.

Viale della Tecnica n° 18
36100 Vicenza - Italy
Tel. +39 0444.287960
Fax +39 0444.287959
info@siser.it - www.siser.it

N.B.

All information given in this sheet are based on our experience.
We always recommend performing a test before starting standard production.
For best results we recommend to store the product away from direct sunlight.