

VIDEOFLEX®

Description

Plotter cut heat seal material with polyester backing. One of the most requested Siser cut materials, due to its resistant softness and feel. Specifically conceived for the sports industry, it is popular among many professional leagues for its high covering power and matt finish.



The material is certified **Öko-Tex® Standard 100 Classe I**

Average thickness: **250 micron**

Basic information

Due to the many different base materials available on the market, the following heat transfer instructions are given as a guideline only:

Plotter settings (eg. with SUMMACUT D60R plotter)

Blade: **new at 50°**

Minimum required pressure: **90 gf**

Transfer setup

Temperature: **150°C**

Time: **15"**

Pressure: **medium (3÷4 bar)**

Application instructions

Mirror cut the material

Weed the exceeding material

Place the material on the garment with its polyester backing

Heat apply

Remove the support cold

Suitable textiles

Cotton, polyester and blends of these materials
(not suited for treated and dye sublimation fabrics)

Washing instructions

Wait **24h** after the heat transfer

80°C Max

Do not use bleach or other aggressive chemical agents

Dry clean: **no**

Tumble dry: **yes**



Siser s.r.l.

Viale della Tecnica n° 18
36100 Vicenza - Italy
Tel. +39 0444.287960
Fax +39 0444.287959
info@siser.it - www.siser.it

N.B.

All information given in this sheet are based on our experience.

We always recommend performing a test before starting standard production.

For best results we recommend to store the product away from direct sunlight.