

Soft-PVC 80µ, white glossy

Kraft paper, permanent

1130 H12 P3

Technical Product Information

F
i
l
m

Grade characteristics

Description	Soft-PVC white glossy
Application	Decorative labels for cosmetics, food.
Coating	With certified Indigo-topcoat
Approvals	Complies with EU-Regulations: Packaging 94/62/EC ; Heavy Metal, PBB and PBDE 2003/11;
Remarks	Suitable for HP Indigo

Physical properties	Value	Unit	Test method
Caliper	80	µm	ISO 534
Stretch at break md	> 160	%	DIN 53455
Tear resistance md	> 26	Mpa	ISO 1924/1

A
d
h
e
s
i
v
e

Description

Permanent adhesive P3:
High transparency, permanent copolymeric acrylate adhesive with controlled initial tack. Complies with the EN 71/3 (application on toys) and the European packaging directive 94/62/EC (heavy metals).

Physical properties	Value	Unit	Test method
Adhesion P3 → permanent	14 ± 6	N/25mm	FTM 1 24h on glass

L
i
n
e
r

Description

Liner H12:
135g/m², chlorine free bleached Kraftliner

Physical properties	Value	Unit	Test method
Substance	135	g/m ²	ISO 536
Caliper	136	µm	ISO 534

Storage and application data

Recommended processing temperature	min. + 5°C
Product application temperature	- 30° up to + 90°C
Life expectancy	1 year
Shelf life at 23°C / 50% r.h.	1 year in original packing *

Warranty

INTERCOAT materials are manufactured according to highest quality standards and pass stringent quality controls prior to despatch. Any material showing an evident defect of manufacturing will be replaced promptly without charge. The wide range of different applications does not allow to test all possibilities of employment. All statements, technical information and recommendations are based on tests and practical experiences and believed to be reliable but do not constitute a guarantee or warranty. Preliminary tests are recommended for each new application. For any need of advise or technical support the INTERCOAT technical department will be pleased to assist.